


ALLEGRI

BY KALCO LIGHTING



MODEL 11804

ASSEMBLY AND DRESSING INSTRUCTIONS

Blending innovative design, cutting-edge technology and the grace and elegance of traditional crystal, ALLEGRI® proudly brings you a new approach to lighting. ALLEGRI® fixtures are made from the finest raw materials and are brought to life through a combination of traditional manufacturing, such as sand casting, hand-forging and technology driven techniques including laser cutting.

Enclosed are detailed instructions on how to properly install your fixture. Please read all instructions carefully. If you need further assistance, please contact the dealer from which you purchased this product or call 866-520-2665 to speak with an ALLEGRI® customer service representative. We hope you enjoy your fixture!

ALLEGRI

BY KALCO LIGHTING

ASSEMBLY AND DRESSING INSTRUCTIONS

WARNING! **CONTENTS ARE FRAGILE** **HANDLE WITH CARE**

THE METAL FRAME, FINISH AND CRYSTAL COMPONENTS OF THIS CHANDELIER ARE VERY DELICATE.
PLEASE EXERCISE EXTREME CAUTION DURING UNPACKING AND INSTALLATION.

PLACE ALL PIECES TOGETHER IN A NUMERICAL ORDER AND IN THE ORIENTATION DEPICTED.
REFER TO THE PARTS LIST TO AVOID ANY CONFUSION BETWEEN PARTS THE PARTS NUMBER MUST COINCIDE.

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY AND PROPERTY DAMAGE. All electrical components must be installed only by a Licensed Electrician.

This product must be installed in accordance with the National Electric Code (NEC), and appropriate local electrical code(s), by a person familiar with the construction and operation of the product and the hazard involved.*

CAUTION: Do not exceed maximum wattage note on fixture. Uses only recommended bulbs with fixture.

GENERAL NOTES

- ❖ For your safety and proper operation of fixture, read and understand all instructions completely before commencing installation.
- ❖ This fixture is suited for dry locations. Never install fixture on damp ceiling; room should be dry and well ventilated.
- ❖ Extreme care should be taken to avoid damage to the surface of lighting fixture and wires. Wearing gloves is recommended for installation.
- ❖ Connect ribbed wire of lighting fixture to live wire, while smooth wire of lighting to neutral. Connect bare copper or silver color ground wire of fixture to the double colored or green wire of outlet box.
- ❖ Use UL LISTED wire nuts for the wiring connections in this fixture. Wrap wire nut connections with UL LISTED electrical tape.
- ❖ Keep lighting away from acid, alkali and other corrosive chemical or gas; clean the fixture with a clean cloth only.
- ❖ Fixture must be firmly secured when installing ceiling tube, chain pipe and other connecting parts.
- ❖ Never cover the lighting fixture when power is connected.
- ❖ Disconnect the power before installing, cleaning and/or replacing light bulb.
- ❖ Extreme care should be taken when installing and cleaning of Glass and/or Crystal Components.
- ❖ This product is rated 110-130V/60HZ bulb 40W Maximum.
- ❖ Save these instructions for future reference.

WARNING

The electricity must be turned off at the main fuse box or circuit breaker before installing this fixture. Turning the power off using the light switch may not be sufficient to prevent electrical shock.


*ALLEGRI will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.

ALLEGRI


BY KALCO LIGHTING

FLUSH PLATE MOUNTING INSTRUCTION

Please note: two or more installers may be needed to perform this fixture installation.



All electrical components must be installed by a licensed electrician in accordance with the National Electric code and the appropriate local electrical codes.




INSTALL FLUSH PLATE AS FOLLOWS:

CAUTION: Make sure power is off at the main breaker prior to installation.
Make sure ceiling can support weight of 200lbs otherwise make ceiling reinforcements.

1. If the installation is made on a concrete ceiling. Place cross bar on position flat to ceiling and mark mounting screw holes to be drilled for anchor screws.
2. If installation is made in drywall or wood make sure reinforcements are made to support fixture's weight.
3. Install cross bar to ceiling make sure fixture mounting screws on cross bar are pointing towards the floor. (use leveler to make sure the fixture mounting screws will match holes in flush plate).

DRIVER WIRE CONNECTION



Connect power supply to (L) and (N) of LED Driver as shown.

Connect LED wire to (-V +V) of driver as shown.

1. Make sure the LED driver is connected inside flush plate as shown.
2. Connect power supply black wire to (L) terminal of the driver
3. Connect power supply white wire to (N) terminal of the driver
4. Connect junction box green ground wire to (\perp) terminal of the driver
5. Connect smooth wire from LED light strip to (-V) terminal of driver
6. Connect ribbed wire from LED light strip to (+V) terminal of driver



ALLEGRI

BY KALCO LIGHTING

FRAME ASSEMBLY INSTRUCTIONS

MODEL 11804

Flush Plate bottom view



4. Install metal frame to flush plate on the floor under installation site, pass ss cables through cable gliders and secure them with locking block and allen key.
5. On fixtures with parallel wires the smooth side goes to white and ribbed side goes to black wire of power supply. On fixtures with colored wires connect black to black, white to white and fixture bare copper ground wire to green wire of junction box.
6. Rise flush plate close enough to ceiling to connect electric wires in junction box, use wire nuts and electrical tape to secure electrical connections.
7. Place flush plate over cross bar matching fixture mounting screws with flush plate holes, pass the mounting screw through holes and secure them with decorative nuts.
8. Adjust fixture ss wires to desired height, cables are 8ft long and can be shortened by pushing the cable gliders tip while pushing ss cables in at the same time. Push cable glider to release ss cable.
9. Install 10 halogen GU10-50W bulbs and turn on.

ALLEGRI

BY KALCO LIGHTING


CRYSTAL DRESSING INSTRUCTION

MODEL 11804

WARNING



Electrical Danger



Turn Power Off

All electrical components must be installed by a licensed electrician in accordance with the National Electric code and the appropriate local electrical codes.







NOTE:

All crystals on this fixture are pre-assembled.



You will need 10 - Cand.Buld
50 Watts Recommended
50 Watts Max
Bulb not included

Code	Qty
A	960



8950

A

ALLEGRI

BY KALCO LIGHTING

LIGHTING CARE INFORMATION

Every ALLEGRI® fixture is of heirloom quality and will last for generations. To ensure it retains its brilliance and splendor for years to come, proper care and regular cleaning are necessary.

It is recommended that ALLEGRI® fixture, and particularly their crystal trim, be lightly dusted with a feather or lambs wool duster, or soft brush every two months, or whenever it appears dull or dusty. A thorough cleaning should be completed every six months.

Before cleaning an ALLEGRI® fixture, first locate the fixture's trim diagram. This will assist in replacing the crystal trim in its proper location after cleaning. Should a replacement trim diagram be required, please call 866-820-2665 to speak with an ALLEGRI® customer service representative, who can provide a new diagram.

ALLEGRI® recommends several different cleaning methods, depending on the type of fixture. Some fixtures can be cleaned with limited removal of crystal, while others must be completely untrimmed.

Place a soft towel or blanket directly beneath the fixture to limit the damage to both the crystal and the surface below the fixture, should a piece of crystal be dislodged during the cleaning process. Extreme care must be taken around any electrical fixture. For personal safety and the safety of the fixture, be sure that the fixture has been turned off. Never rotate or spin the fixture as this can cause the fixture to lose support and fall. Instead, move around the fixture while cleaning.

White Glove Method

Prepare a cleaning solution of one part isopropyl alcohol to three parts distilled water and place in a clean spray bottle. Do not use packaged cleaning fluids, as many of these contain ammonia, which may degrade the finish of the fixture and the quality of the crystal.

Wearing white cotton gloves, spray one glove with the solution and keep one dry. Gently polish each crystal with the damp glove and immediately wipe it with the dry glove. Do not tug or pull on the crystal, as this may cause the connectors to chip or crack the crystal, or dislodge it from the fixture.

Warning: To reduce the risk of personal injury due to fire and/or electric shock, never spray solution at or near the fixture.

Crystal Removal Method

Gently remove trim and hand-wash the crystal in lukewarm water using a mild detergent. Rinse in clean water and dry with a soft clean cloth. Do not soak finished crystal such as SWAROVSKI ELEMENTS Colors: Teak, Golden Shadow or Silver Shade, for extended periods, as this may degrade the crystal's finish.

With the fixture untrimmed and turned off, wipe the frame, including the light bulbs once they are completely cool, with a soft cloth.

Wearing white gloves, finger-cots or using a soft clean cloth, gently replace the trim as directed in the trim diagram.